

Adhesive Lined Heat Shrink Terminals

EXPANDED OFFERING

- Heat activated adhesive built into the sleeve of the heat shrink tubing
- Shrinks to form a water tight seal and ultimate vibration and strain relief
- Tinned for corrosion resistance
- Pure copper for maximum current flow
- Brazed seam for maximum strength
- UL listed and CSA recognized
- Shrinks at 275°F / 135°C



Heat Shrink Ring Terminals

- UL 486A

AWG	Screw Size	Qty/ Pkg	Part #
22-18 0.3-0.8 mm ²	#8 4 mm	3	310203
		25	310225
		100	310299
	#10 4.8 mm	3	310303
		25	310325
		100	310399
	1/4" 6.4 mm	3	310403
		25	310425
		100	310499
	5/16" 7.9 mm	3	310503
		25	310525
		100	310599
16-14 1-2 mm ²	#8 4 mm	3	311203
		25	311225
		100	311299
	#10 4.8 mm	3	311303
		25	311325
		100	311399
	1/4" 6.4 mm	3	311403
		25	311425
		100	311499
	5/16" 7.9 mm	3	311503
		25	311525
		100	311599
	3/8" 9.5 mm	3	311603
		25	311625
		100	311699

AWG	Screw Size	Qty/ Pkg	Part #
12-10 3-5 mm ²	#8 4 mm	3	312203
		25	312225
		100	312299
	#10 4.8 mm	3	312303
		25	312325
		100	312399
	1/4" 6.4 mm	3	312403
		25	312425
		100	312499
	5/16" 7.9 mm	3	312503
		25	312525
		100	312599
8 8 mm ²	3/8" 9.5 mm	3	312603
		25	312625
		100	312699
	#10 4.8 mm	3	321303
		25	321325
		100	321399
	1/4" 6.4 mm	3	321403
		25	321425
		100	321499
	5/16" 7.9 mm	3	321503
		25	321525
		100	321599
	3/8" 9.5 mm	3	321603
		25	321625
		100	321699
	1/2" 12.7 mm	3	321703
		25	321725

Related Products



Crimping Tools
pages 53-55



Heat Tools
page 56