## SPINNAKER POLE ACCESSORIES

#### **ALUMINUM TUBING**

Clear anodized to military specification (triple commercial). Prime marine alloy 6063-T6. All tubing sold in stock lengths.

Part No.	O.D.	Stock Lengths	Wall	I.D.	Wt./ Ft.	Part No.	O.D.	Stock Lengths	Wall	I.D.	Wt./ Ft.
500018	1-1/2"	22'6"	.065"	1.370"	.35 lbs	301065	3"	11'2"	.083"	2.835"	1.00 lb
500014	1-1/4"	12'	.050"	1.150"	.22 lbs	301072	3"	12'2"	.083"	2.835"	1.00 lb
408002	1-1/2"	7'2"	.065"	1.370"	.35 lbs	301019	3"	13'	.083"	2.835"	1.00 lb
301005	1-1/2"	7'6"	.065"	1.370"	.35 lbs	301063	3"	16'	.083"	2.835"	1.00 lb
500020	2"	21'6"	.065"	1.870"	.47 lbs	301030	3"	23'4"	.083"	2.835"	1.28 lb
408003	2"	7'2"	.065"	1.870"	.47 lbs	301061	3-1/2"	24'4"	.120"	3.260"	1.50 lb
401004	2"	9'1"	.065"	1.870"	.47 lbs	403004	3-1/2"	12'2"	.120"	3.260"	1.50 lb
301058	2-1/2"	20'2"	.083"	2.334"	.74 lbs	301059	3-1/2"	14'	.120"	3.260"	1.50 lb
301056	2-1/2"	9'	.083"	2.334"	.74 lbs	301024	3-1/2"	15'	.120"	3.260"	1.50 lb
301057	2-1/2"	11'2"	.083"	2.334"	.74 lbs	301003	4"	20'	.120"	3.750"	1.72 lb
						* Custom Tu	ıbing is als	so available by t	the foot, ca	all for pricing	1

#### **VERTICAL POLE STORAGE CAR**

This mast fitting is a simple solution to vertical pole storage problems. The VPC-125 retains the upper end of the stowed pole on the mast centerline. The chock slides on the track and eliminates rattle, vibration and binding of the pole end. All four cars fit 1-1/4" T-Track. Available in four sizes; this mast fitting can be rigged with our FC-125 and T-125 mast cars.



Part No.	Model No.
335100	VPC-125-250
335101	VPC-125-300
335102	VPC-125-350
335103	VPC-125-400

#### **ADAPTING COLLARS**

For sleeving Forespar® spinnaker pole end-fittings for use on larger diameter tubing, and other applications.



Part No.	Model No.	Adapts:
304049	AC-2 "ULTRA"	2.00" to 2.50"
304048	AC-3 "ULTRA"	3.00" to 3.50"
304085	"ULTRA"	3.00" to 4.00"
304086	"ULTRA"	3.00" to 4.50"

STANCHION MOUNTED POLE CHOCKS

weather-resistant urethane and mount easily onto 1" stanchions

(Chocks are sold individually — two chocks are needed for each

pole.) For spinnaker or whisker poles. Ideal for reaching struts!

Clear the decks! Now you can stop stumbling over deck

mounted poles. These chocks are molded from durable,

- no drilling necessary. For poles 2" to 3-1/2" in diameter.

#### **DECK CHOCKS**

Our deck chocks stow our spinnaker poles or whisker poles on the deck. We strongly recommend poles be stored on deck for heavy weather. The "Ultra" deck chocks will accept all Forespar® pole fittings. Designed and made from Marelon for rugged use and use a "snag-proof" low profile design.



DC-2-S

# .

DC-2



DC-TS











Part No.	Model No.	Des
300002	DC-2 "Ultra"	(For L
300013	DC-TS "Ultra"	(For 7
300028	DC-TS-S	(Stair
300029	DC-2-S	(S. st

Description				
(For UXP, UTR, GP & UGPS end fittings)				
(For TS & UTS end fittings)				
(Stainless steel, for UTS & TS ends)				
(S. steel, for UXP, UTR, UGPS & GP ends)				

Pai	rt No.	Model No.	For Pole Dia
300	050	SC 200	2"
300	042	SC 250	2-1/2"
300	043	SC 300	3"
300	044	SC 350	3-1/2"

### **MAST MOUNTED CHOCKS**

(For Vertical Pole Mounting on the Mast)
Molded from durable high tech urethane, these chocks allow for stowing the pole vertically against the face of the mast. Off the deck and out of the way! Two MPC chocks mounted 2-3 feet apart will help stop the pole from rattling.



Part No.	Model No.	Description
300070	MPC 200	2" Mast Pole Chock
300071	MPC 250	2-1/2" Mast Pole Chock
300072	MPC 300	3" Mast Pole Chock
300073	MPC 350	3-1/2" Mast Pole Chock
300074	MPC 400	4" Mast Pole Chock