

## VENTED LOOPS

Installing one of our vented loops will ensure that fluids will not siphon from tank to tank. Vented Loops are commonly used in the marine toilet system and engine cooling system. The simple valve system incorporated in the top of the loop allows air to enter the line when not in use, yet effectively seals as water or other fluid passes through. Molded in Marelon®, neither vent nor loop will corrode. The duckbill one way valve is designed to seal properly if particulate matter is present in fluids. The new MF-846 vent barb assembly option can be used in lieu of the standard MF-841 cap/duckbill. This option allows venting to the outside of the hull via a 1/4" (6.35mm) hose.


**NEW**  
**White Color**  
**Available**

| Part No. | Model No.           | Barb Size          | Height            | Width             |
|----------|---------------------|--------------------|-------------------|-------------------|
| 903000   | MF 840              | 1-1/2" (38.1mm)    | 5-1/4" (133.35mm) | 7-3/4" (196.85mm) |
| 903000W  | MF 840 <b>White</b> | 1-1/2" (38.1mm)    | 5-1/4" (133.35mm) | 7-3/4" (196.85mm) |
| 903001   | MF 842              | 3/4" (19.05mm)     | 4-1/2" (114.3mm)  | 3-3/4" (95.25mm)  |
| 903001W  | MF 842 <b>White</b> | 3/4" (19.05mm)     | 4-1/2" (114.3mm)  | 3-3/4" (95.25mm)  |
| 903002   | MF 841              | Vent Cap Assembly  |                   |                   |
| 903002W  | MF 841 <b>White</b> | Vent Cap Assembly  |                   |                   |
| 903003   | MF-843              | 5/8" (15.87mm)     | 4-1/2" (114.3mm)  | 4" (101.6mm)      |
| 903004   | MF-846              | Vent Barb Assembly |                   |                   |
| 903007   | MF-844              | 1" (25.4mm)        | 7" (177.8mm)      | 9" (228.6mm)      |
| 903007W  | MF-844 <b>White</b> | 1" (25.4mm)        | 7" (177.8mm)      | 9" (228.6mm)      |
| 903008   | MF-845              | 1/2" (12.7mm)      | 5-1/4" (133.35mm) | 4-1/4" (107.95mm) |
| 903008W  | MF-845 <b>White</b> | 1/2" (12.7mm)      | 5-1/4" (133.35mm) | 4-1/4" (107.95mm) |
| 903018   | MF-847              | 1-1/8" (28.57mm)   | 7" (177.8mm)      | 9" (228.6mm)      |
| 903011   | MF-839              | 1-1/4" (28.57mm)   | 7" (177.8mm)      | 9" (228.6mm)      |
| 903011W  | MF-839 <b>White</b> | 1-1/4" (28.57mm)   | 7" (177.8mm)      | 9" (228.6mm)      |

MF-846  
VENT  
BARB



MF-841  
VENT CAP  
ASSEMBLY



## 'Y' VALVES & CONNECTORS

Forespar® 'Y'-Valves and Connectors are molded from Marelon®. Offering an improved, stronger handle design, our valves are available in 1" (25.4mm) and 1-1/2" (38.1mm) barb size. 'Y'-Valves are an essential piece of equipment when the flow of water or other fluids are required to be conveniently diverted, as in a marine head application where a holding tank is utilized. They are easily mounted to a bulkhead. The valves are operated by a simple 120° movement. Positive stops are provided between positions. Replacement parts are available.

Our 'Y' Connectors can be used for connecting fluid lines. End plate may be removed for blockage relief etc. O-ring seal ensures leak free performance and is safe under pressure working conditions up to 40 P.S.I. Available with or without mounting flange.



### 'Y' CONNECTORS

| Part No. | Model No. | Flange | Barb Size       |
|----------|-----------|--------|-----------------|
| 902002   | HYCF 16   | Yes    | 1" (25.4mm)     |
| 902003   | HYC 16    | No     | 1" (25.4mm)     |
| 902004   | HYCF 24   | Yes    | 1-1/2" (38.1mm) |
| 902005   | HYC 24    | No     | 1-1/2" (38.1mm) |

### 'Y' VALVES

| Part No. | Model No.                             | Barb Size        |
|----------|---------------------------------------|------------------|
| 902000   | MF 852                                | 1-1/2" (38.1mm)  |
| 902001   | MF 853                                | 1" (25.4mm)      |
| 902006   | 'Y'-Valve Parts Kit (fits 1 & 1-1/2") |                  |
| 902007   | MF 854                                | 3/4" (19.05mm)   |
| 902008   | MF 855                                | 1-1/8" (28.57mm) |

**IT IS NOT RECOMMENDED TO INSTALL Y-VALVES BELOW THE WATERLINE**