

# MKIV Unit 0

Typical Boat Length 6.5 - 9.1 m (22' - 30')

Wire Ø (1 x 19 SS)	Rod Ø	Clevis pin Ø
4, 5, 6 mm (5/32", 3/16", 7/32")	-4, -6 (4.37, 5.03 mm)	7.9, 9.5, 11.1 mm (5/16", 3/8", 7/16")

**Headstay Length Standard 11.77 m (38'7"); max 13.9 m (45'7")**

Part No.	Description
7410.10	Furling system

### Toggle Assembly Required - sold separately

7410.20 5/16	Eye/jaw reversible toggle assembly with 7.9 mm (5/16") clevis pin
7410.20 3/8	Eye/jaw reversible toggle assembly with 9.5 mm (3/8") clevis pin
7410.20 7/16	Eye/jaw reversible toggle assembly with 11.1 mm (7/16") clevis pin

### Optional Parts

7410.30	Extra 2.13 m (7") luff foil extrusion
7410.31	Extra 165 mm (6 1/2") connector with bushings
7420 -4	-4 rod adaptor stud (thread Ø UNF 7/16")*
7421 -6	-6 rod adaptor stud (thread Ø UNF 7/16")*

\*Use with conventional turnbuckle.

# MKIV Unit 1

Typical Boat Length 8.3 - 11 m (28' - 36')

Ø Cable (1 x 19 SS)	Ø Varilla	Ø Pasador
6, 7, 8 mm (1/4", 9/32", 5/16")	-8, -10, -12 (5.72, 6.35, 7.14 mm)	12.7, 15.9 mm (1/2", 5/8")

**Headstay Length Standard 13.99 m (45'11"); max 16.12 m (52'11")**

Part No.	Description
7411.10	Furling system

### Toggle Assembly Required - sold separately

7411.20 1/2	Eye/jaw reversible toggle assembly with 12.7 mm (1/2") clevis pin
7311.20 1/2	Jaw/jaw toggle assembly with 12.7 mm (1/2") clevis pin
7311.20 5/8	Stud/jaw toggle assembly with 15.9 mm (5/8") clevis pin (thread Ø UNF 5/8" LH)
7311.21 1/2	Long link plate with toggle assembly with 12.7 mm (1/2") clevis pin
7311.21 5/8	Long link plate with toggle assembly with 15.9 mm (5/8") clevis pin

### Optional Parts

7411.30	Extra 2.13 m (7") luff foil extrusion
7411.31	Extra 178 mm (7") connector with bushings
7422 -8	-8 rod adaptor stud (thread Ø UNF 1/2")*
7423 -10	-10 rod adaptor stud (thread Ø UNF 1/2")*
7424 -12	-12 rod adaptor stud (thread Ø UNF 5/8")*

\*Use with conventional turnbuckle.



7410.30  
7411.30



7410.31  
7411.31

7420 -4  
7421 -6  
7422 -8  
7423 -10  
7424 -12



7410.20 5/16  
7410.20 3/8  
7410.20 7/16  
7411.20 1/2



7311.20 1/2



7311.20 5/8



7311.21 1/2  
7311.21 5/8