



	M330	M330G	M424G	M400BB	M510/M510 AIS	M605/M605 AIS
Specifications						
RF Output Power	25 W / 1 W	25 W / 1 W	25 W / 1 W	25 W / 1 W	25 W / 1 W	25 W / 1 W
AF Output Power	4.5 W	4.5 W	4 W	2 W	15 W	15 W
IP Rating	IPX7 (1 m depth/30 min)	IPX8 (1.5 m depth/30 min)	IPX7 (1 m depth/30 min)	IPX7 (1 m depth/30 min)	IP68 (1.6 m depth/30 min)	IPX8 (1.6 m depth/30 min)
Mil Spec Rating	NA	NA	NA	NA	810-C/D/E/F	810-C/D/E/F
Commandmic™	NA	NA	HM-195GB/SW	HM-195B/SW	HM-195GB/SW	HM-195GB/SW
OPC Cords*	NA	NA	OPC-1540 OPC-1541	OPC-1540 OPC-1541	OPC-1540 OPC-1541	OPC-1540 OPC-1541 OPC-2384
Features						
NMEA 2000®	NA	NA	NA	NA	(O) CT-M500	√
NMEA 0183	√	√	√	√	√	√
DSC	√	√	√	√	√	√
Aquaquake™	√	√	√	√	√	√
Tag Scan/ Favorite Channel	√	√	√	√	√	√
Dual/Tri-watch	√	√	√	√	√	√
Priority Scan	√	√	√	√	√	√
RX Weather Channel	√	√	√	√	√	√
GPS Antenna	NA	Internal & External UX-241 Option	Internal Only	NA	Internal & External Antenna	GNSS Antenna Included
AIS (RX)	MA-510TR	MA-510TR	MA-510TR	MA-510TR	MA-510TR M510 AIS (RX)	MA-510TR M605 AIS (RX)
AIS	NA	NA	NA	NA	√	√
Hailer/Foghorn	NA	NA	√	√	(O) CT-M500	√
Microphones - Removable	NA	NA	NA	NA	√	√
Command Head	NA	NA	NA	NA	NA	(O) RC-M605
Commandmic™	NA	NA	√	√	√	√*
Rear Mic	NA	NA	√**	NA	√**	√**
Speaker Mic	NA	NA	HM-195B	NA	HM-205RB	HM-205RB
Active Noise Cancelling	NA	NA	√	√	√	√
Remote Station	NA	NA	NA	NA	NA	RC-M600
IOS/Android APP	NA	NA	NA	NA	RS-M500	NA

NOTES

*Use one of the three combinations when setting up your M605:

M605 + three COMMANDMICS

M605 + two COMMANDMICS + one Command Head

M605 + two Command Heads + one COMMANDMIC

**Rear mic requires OPC-1000