

Dual tone horn with a sealed sound unit. 18.8 stainless steel cover, diaphragm and mounting bracket. 12 volt, pre-wired.

For a **FREE** catalog of Marinco Recreational Group products, contact your local dealer or Marinco.

For more information and installation guides visit our website: www.marinco.com



2655 Napa Valley
Corporate Drive
Napa, California 94558

Phone: 707-226-1900
Fax: 707-226-9610
Website: www.marinco.com

Made in Thailand
18001, (03-01)
Product No. 10001



INSTALLATION AND WIRING INSTRUCTIONS

INSTALLATION:

1. Select an installation position on the boat where a minimum of spray will hit the horn when the boat is underway.
 2. At the same time, select an installation position which will assure the shortest possible length of wire from the horn to the power source.
 3. Use the holes in the bracket as a template for the location of the mounting points and drill holes for the bracket and wiring.
 4. Insert wiring through the deck, then install the bracket to the deck surface. Caulk all installation holes with silicone sealer.
- The horns should point slightly downward to permit water drainage.**

WIRING:

1. Connect wiring as illustrated in the diagram.
2. Cut wires of sufficient length to avoid any tension at the connecting points.
3. Use flexible stranded wire of sufficient size as per wiring chart.
4. If horn volume is weak, recheck wiring connections and around wire. If horn does not work at all, check the fuse.

RECOMMENDED WIRE SIZES FOR 12 VOLT OPERATION

Wire Length**	Wire Size	Wire Length**	Wire Size
25 feet	16 AWG*	0-8 meters	1.5 mm
3-40 feet	14 AWG	9-12 meters	1.9 mm
1-60 feet	12 AWG	13-18 meters	2.3 mm
over 60 feet	10 AWG	over 18 meters	3.0 mm

WG: American Wire Gauge
*As measured from the battery to the horn and back to the battery (round trip).

Horn wiring has no polarity, negative or positive can be attached to either wire.

