



# **Vertical Mount Side Lights**

## 2-mile (USCG 2nm) Certified

Use on Power Driven Vessels Under 20m (65.6 ft.) in Length

Material: Zinc Alloy Finish: Chrome Plated

Length: 3-1/2", Width: 2-1/4", Projection: 1-3/8" Dimensions:

Screw Size:

Contacts: **Gold Plated** 

Voltage: 12V (Bulb Included) Wattage: 8 watts (each light) Amperage: .70 amps (each light)

**OEM Bulk Pkg.\* Finish** Chrome 0264M0012V







## 1-mile (USCG 1nm) Certified

Use on Sail or Power Driven Vessels Under 12m (39.4 ft.) in Length Brass or Stainless Steel Top, Polymer Base Material:

Finish: Chrome Plated or Polished

Dimensions: Length: 4-1/4", Width: 2-3/8", Projection: 1-9/16"

Screw Size: #4

Contacts: **Gold Plated** 

Voltage: 12V (Bulb Included) Wattage: 10 watts (each light) Amperage: .80 amps (each light)

**Finish** Retail Pkg.\* **OEM Bulk Pkg.\*** Chrome 0955DP0CHR 0955000CHR Polished SS 0955DP0STS 0955000STS

\*Sold in pairs.







## 1-mile Certified A-16 for replacement use only

Use on Power Driven Vessels Under 12m (39.4 ft.) in Length

Material: Zinc Allov Top, Vinvl Gasket

**Chrome Plated** Finish:

Dimensions: Length: 5-1/2", Width: 3-1/8", Projection: 1-3/4"

**Gold Plated** Contacts:

Screw Size:

12V (Bulb Included) Voltage: 10 watts (each light) Wattage: Amperage: .80 amps (each light)

**Finish** Retail Pkg.\* Chrome Zinc 1264DP0CHR





NOTE: All the above can also be used as 24-volt A.B.Y.C. A-16 certified lights on boats built prior to 11/1/03. Replace the bulbs provided on Figs. 0955 & 1264 with Cat. No. 0072DP1CLR and Fig. 0264 with 0072DP8CLR 24-volt bulbs. Contact us for 24-volt applications on new construction.

Fig. 0264: Green Lens Only: 0277DPGLNS. Red Lens Only: 0277DPRLNS. Base w/Socket Assy: 0254BLK99A. Bulbs: 0071DP8CLR

### **Spare Parts Information**

Fig. 1264: Green Side Light: 1264G00CHR. Red Side Light: 1264R00CHR. Lens Set: 1264DP0LNS. Socket Assembly: 1264DP099A. Bulbs: 0071DP0CLR.

Chrome Brass Green Side Light: 0955G00CHR. Chrome Brass Red Side Light: 0955R00CHR. Stainless Green Side Light: 0955G00STS. Stainless Red Side Light: 0955R00STS. Base with Socket Assembly: 095500099A. Lens Set: 0260DP0LNS.

Fig. 1264

Bulbs: 0071DP0CLR.







Fig. 0260DP0LNS

