

 Safety Data Sheet

 According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous

 Products Regulation (February 11, 2015).

 Revision Date: 03/14/2017
 Date of Issue: 03/14/2017
 Version: 1.0

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture Product Name: Non-Skid Deck Wax Product Code: 973XX

Intended Use of the Product

Wax

Name, Address, and Telephone of the Responsible Party

Starbrite[®] Inc. 4041 SW 47th Avenue Fort Lauderdale, FL 33314

(954)587-6280

www.starbrite.com Emergency Telephone Number

Emergency Number : US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION Classification of the Substance or Mixture GHS-US/CA Classification Eve Dam. 1 H318 Full text of hazard classes and H-statements : see section 16 Label Elements **GHS-US/CA** Labeling Hazard Pictograms (GHS-US/CA) Signal Word (GHS-US/CA) : Danger Hazard Statements (GHS-US/CA) : H318 - Causes serious eye damage. **Precautionary Statements (GHS-US/CA)** : P280 - Wear protective gloves, protective clothing, and eye protection. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER or doctor. **Other Hazards**

Exposure may aggravate pre-existing eye, skin, or respiratory conditions. May cause skin dryness or cracking.

Unknown Acute Toxicity (GHS-US/CA)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>Mixture</u>

| Name | Product Identifier | % * | GHS Ingredient Classification |
|---|---------------------|-------------|-------------------------------|
| Petroleum distillates, hydrotreated light | (CAS No) 64742-47-8 | 1.75145 - | Asp. Tox. 1, H304 |
| | | 4.50725 | |
| Poly(oxy-1,2-ethanediyl), .alpha[3,5- | (CAS No) 60828-78-6 | 0.5 - 3 | Eye Dam. 1, H318 |
| dimethyl-1-(2-methylpropyl)hexyl]omega | | | Aquatic Chronic 3, H412 |
| hydroxy- | | | |
| 2-Butoxyethanol | (CAS No) 111-76-2 | 0.35 - 1.35 | Flam. Liq. 4, H227 |
| | | | Acute Tox. 4 (Oral), H302 |
| | | | Acute Tox. 4 (Dermal), H312 |

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | | Acute Tox. 4 (Inhalation:vapor), H332 Skin Irrit. 2, H315 Eve Irrit. 2A, H319 |
|---|---------------------|--------------|--|
| Poly(oxy-1,2-ethanediyl), .alpha[3-[1,3,3,3- tetramethyl-1- [(trimethylsilyl)oxy]disiloxanyl]propyl]- .omegahydroxy- | (CAS No) 67674-67-3 | 0.35 - 1.3 | Acute Tox. 4 (Inhalation:dust,mist), H332 Eye Dam. 1, H318 Aquatic Chronic 2, H411 |
| Poly(oxy-1,2-ethanediyl), .alphasulfo- .omega[(1,1,3,3-tetramethylbutyl)phenoxy]- , sodium salt | (CAS No) 55348-40-8 | 0.025 - 0.15 | Skin Irrit. 2, H315 Eye Dam. 1, H318 |
| Polyethylene glycol | (CAS No) 25322-68-3 | 0.005 - 0.1 | STOT SE 3, H335 |
| Isopropyl alcohol | (CAS No) 67-63-0 | 0.005 - 0.1 | Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336 |

Full text of H-phrases: see section 16

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

SECTION 4: FIRST AID MEASURES

Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes serious eye damage.

Inhalation: Prolonged exposure may cause irritation.

Skin Contact: Prolonged exposure may cause skin irritation. May cause an allergic reaction in sensitive individuals.

Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva.

Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: None known.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. Remove containers from fire area if this can be done without risk. Do not breathe fumes from fires or vapors from decomposition.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection. **Hazardous Combustion Products**: Thermal decomposition generates: Carbon oxides (CO, CO₂). Nitrogen oxides. Sulfur oxides. Silicon oxides. Hydrocarbons. Halogenated Compounds. Metal oxides. Oxides of copper. Unidentified organic compounds. Formaldehyde.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe vapor, mist or spray. Do not get in eyes, on skin, or on clothing.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Precautions for Safe Handling: Obtain special instructions before use. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid breathing vapors, mist, spray. Do not get in eyes, on skin, or on clothing. Use appropriate personal protective equipment (PPE).

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Containers which are opened should be properly resealed and kept upright to prevent leakage. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Protect from freezing.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Water reactive materials. Reducing agents. Peroxides. Specific End Use(s)

Wax

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

| Polyethylene glycol (25322-68-3) | | |
|----------------------------------|-----------------------------------|---|
| USA AIHA | WEEL TWA (mg/m³) | 10 mg/m ³ (MW>200, aerosol) |
| Isopropyl alcohol (67-63-0) | | |
| Mexico | OEL TWA (mg/m³) | 980 mg/m ³ |
| Mexico | OEL TWA (ppm) | 400 ppm |
| Mexico | OEL STEL (mg/m³) | 1225 mg/m ³ |
| Mexico | OEL STEL (ppm) | 500 ppm |
| USA ACGIH | ACGIH TWA (ppm) | 200 ppm |
| USA ACGIH | ACGIH STEL (ppm) | 400 ppm |
| USA ACGIH | ACGIH chemical category | Not Classifiable as a Human Carcinogen |
| USA ACGIH | Biological Exposure Indices (BEI) | 40 mg/l Parameter: Acetone - Medium: urine - Sampling |

Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | time: end of shift at end of workweek (background, |
|----------------------------|---------------------------------------|---|
| | | nonspecific) |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 980 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 400 ppm |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 980 mg/m ³ |
| USA NIOSH | NIOSH REL (TWA) (ppm) | 400 ppm |
| USA NIOSH | NIOSH REL (STEL) (mg/m ³) | 1225 mg/m ³ |
| USA NIOSH | NIOSH REL (STEL) (ppm) | 500 ppm |
| USA IDLH | US IDLH (ppm) | 2000 ppm (10% LEL) |
| Alberta | OEL STEL (mg/m ³) | 984 mg/m ³ |
| Alberta | OEL STEL (ppm) | 400 ppm |
| Alberta | OEL TWA (mg/m ³) | 492 mg/m ³ |
| Alberta | OEL TWA (ppm) | 200 ppm |
| British Columbia | OEL STEL (ppm) | 400 ppm |
| British Columbia | OEL TWA (ppm) | 200 ppm |
| Manitoba | OEL STEL (ppm) | 400 ppm |
| Manitoba | OEL TWA (ppm) | 200 ppm |
| New Brunswick | OEL STEL (mg/m ³) | 1230 mg/m ³ |
| New Brunswick | OEL STEL (ppm) | 500 ppm |
| New Brunswick | OEL TWA (mg/m ³) | 983 mg/m ³ |
| New Brunswick | OEL TWA (ppm) | 400 ppm |
| Newfoundland & Labrador | OEL STEL (ppm) | 400 ppm |
| Newfoundland & Labrador | OEL TWA (ppm) | 200 ppm |
| Nova Scotia | OEL STEL (ppm) | 400 ppm |
| Nova Scotia | OEL TWA (ppm) | 200 ppm |
| Nunavut | OEL STEL (ppm) | 400 ppm |
| Nunavut | OEL TWA (ppm) | 200 ppm |
| Northwest Territories | OEL STEL (ppm) | 400 ppm |
| Northwest Territories | OEL TWA (ppm) | 200 ppm |
| Ontario | OEL STEL (ppm) | 400 ppm |
| Ontario | OEL TWA (ppm) | 200 ppm |
| Prince Edward Island | OEL STEL (ppm) | 400 ppm |
| Prince Edward Island | OEL TWA (ppm) | 200 ppm |
| Québec | VECD (mg/m ³) | 1230 mg/m ³ |
| Québec | VECD (ppm) | 500 ppm |
| Québec | VEMP (mg/m ³) | 985 mg/m ³ |
| Québec | VEMP (ppm) | 400 ppm |
| Saskatchewan | OEL STEL (ppm) | 400 ppm |
| Saskatchewan | OEL TWA (ppm) | 200 ppm |
| Yukon | OEL STEL (mg/m³) | 1225 mg/m ³ |
| Yukon | OEL STEL (ppm) | 500 ppm |
| Yukon | OEL TWA (mg/m³) | 980 mg/m ³ |
| Yukon | OEL TWA (ppm) | 400 ppm |
| 2-Butoxyethanol (111-76-2) | | |
| Mexico | OEL TWA (mg/m³) | 120 mg/m ³ |
| Mexico | OEL TWA (ppm) | 26 ppm |
| Mexico | OEL STEL (mg/m ³) | 360 mg/m ³ |
| Mexico | OEL STEL (ppm) | 75 ppm |
| USA ACGIH | ACGIH TWA (ppm) | 20 ppm |
| USA ACGIH | ACGIH chemical category | Confirmed Animal Carcinogen with Unknown Relevance to Humans |
| USA ACGIH | Biological Exposure Indices (BEI) | 200 mg/g Kreatinin Parameter: Butoxyacetic acid with |
| 03/14/2014 IOKTT.B-CC | EN (English US) | 4/12 |

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | hydrolysis - Medium: urine - Sampling time: end of shift |
|------------------------------|--------------------------------------|--|
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 240 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 50 ppm |
| USA OSHA | Limit value category (OSHA) | prevent or reduce skin absorption |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 24 mg/m ³ |
| USA NIOSH | NIOSH REL (TWA) (ppm) | 5 ppm |
| USA IDLH | US IDLH (ppm) | 700 ppm |
| Alberta | OEL TWA (mg/m³) | 97 mg/m³ |
| Alberta | OEL TWA (ppm) | 20 ppm |
| British Columbia | OEL TWA (ppm) | 20 ppm |
| Manitoba | OEL TWA (ppm) | 20 ppm |
| New Brunswick | OEL TWA (mg/m³) | 121 mg/m ³ |
| New Brunswick | OEL TWA (ppm) | 25 ppm |
| Newfoundland & Labrador | OEL TWA (ppm) | 20 ppm |
| Nova Scotia | OEL TWA (ppm) | 20 ppm |
| Nunavut | OEL STEL (ppm) | 30 ppm |
| Nunavut | OEL TWA (ppm) | 20 ppm |
| Northwest Territories | OEL STEL (ppm) | 30 ppm |
| Northwest Territories | OEL TWA (ppm) | 20 ppm |
| Ontario | OEL TWA (ppm) | 20 ppm |
| Prince Edward Island | OEL TWA (ppm) | 20 ppm |
| Québec | VEMP (mg/m ³) | 97 mg/m³ |
| Québec | VEMP (ppm) | 20 ppm |
| Saskatchewan | OEL STEL (ppm) | 30 ppm |
| Saskatchewan | OEL TWA (ppm) | 20 ppm |
| Yukon | OEL STEL (mg/m ³) | 720 mg/m ³ |
| Yukon | OEL STEL (ppm) | 150 ppm |
| Yukon | OEL TWA (mg/m³) | 240 mg/m ³ |
| Yukon | OEL TWA (ppm) | 50 ppm |
| Petroleum distillates, hydro | treated light (64742-47-8) | |
| British Columbia | OEL TWA (mg/m ³) | 200 mg/m ³ (application restricted to conditions in which |
| | | there are negligible aerosol exposures) |

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

Other Information: When using, do not eat, drink or smoke

| Information on Basic Physical and Chemical Properties |
|---|
| |

Liquid

:

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| Odor | : Characteristic |
|--|---------------------------|
| Odor Threshold | : Not available |
| рН | : 6-8 |
| Evaporation Rate | : Not available |
| Melting Point | : Not available |
| Freezing Point | : Not available |
| Boiling Point | : > 93.3 °C (> 199.94 °F) |
| Flash Point | : > 93.3 °C (> 199.94 °F) |
| Auto-ignition Temperature | : Not available |
| Decomposition Temperature | : Not available |
| Flammability (solid, gas) | : Not available |
| Lower Flammable Limit | : Not available |
| Upper Flammable Limit | : Not available |
| Vapor Pressure | : Not available |
| Relative Vapor Density at 20°C | : Not available |
| Relative Density | : Not available |
| Specific Gravity | : 1.022 |
| Solubility | : Not available |
| Partition Coefficient: N-Octanol/Water | : Not available |
| Viscosity | : Not available |

SECTION 10: STABILITY AND REACTIVITY

<u>Reactivity</u>: Hazardous reactions will not occur under normal conditions.

<u>Chemical Stability</u>: Stable under recommended handling and storage conditions (see section 7).

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

<u>Conditions to Avoid</u>: Direct sunlight, extremely high or low temperatures, and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Water reactive materials. Reducing agents. Peroxides.

Hazardous Decomposition Products: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product Acute Toxicity (Oral): Not classified Acute Toxicity (Dermal): Not classified Acute Toxicity (Inhalation): Not classified LD50 and LC50 Data: Not available Skin Corrosion/Irritation: Not classified pH: 6 - 8 Eye Damage/Irritation: Causes serious eye damage. **pH:** 6 - 8 Respiratory or Skin Sensitization: Not classified Germ Cell Mutagenicity: Not classified Carcinogenicity: Not classified Specific Target Organ Toxicity (Repeated Exposure): Not classified Reproductive Toxicity: Not classified Specific Target Organ Toxicity (Single Exposure): Not classified Aspiration Hazard: Not classified Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation. Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation. May cause an allergic reaction in sensitive individuals. Symptoms/Injuries After Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva. Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| Chronic Symptoms: None known. |
|--|
| Information on Toxicological Effects - Ingredient(s) |

| Information on Toxicological Effects - Ingredient(s) | | |
|--|---|--|
| LD50 and LC50 Data: | | |
| Poly(oxy-1,2-ethanediyl), .alpha[3,5-dimethyl-1-(2-methylpropyl)hexyl]omegahydroxy- (60828-78-6) | | |
| LD50 Oral Rat | 5650 mg/kg | |
| LD50 Dermal Rabbit | 4780 μl/kg | |
| Poly(oxy-1,2-ethanediyl), .alpha[3-[1,3,3,3-tetramethyl-1- | -[(trimethylsilyl)oxy]disiloxanyl]propyl]omegahydroxy- (67674-67-3) | |
| ATE US/CA (dust, mist) | 1.50 mg/l/4h | |
| Polyethylene glycol (25322-68-3) | | |
| LD50 Oral Rat | 22 g/kg | |
| LD50 Dermal Rabbit | > 20 ml/kg | |
| Isopropyl alcohol (67-63-0) | | |
| LD50 Dermal Rabbit | 4059 mg/kg | |
| LC50 Inhalation Rat | 72600 mg/m ³ (Exposure time: 4 h) | |
| LC50 Inhalation Rat | 72.5 mg/l/4h | |
| 2-Butoxyethanol (111-76-2) | | |
| LD50 Oral Rat | 470 mg/kg | |
| LD50 Dermal Rabbit | > 841 mg/kg | |
| LC50 Inhalation Rat | 2.2 mg/l/4h | |
| LC50 Inhalation Rat | 450 ppm/4h | |
| ATE US/CA (dermal) | 1,100.00 mg/kg body weight | |
| Petroleum distillates, hydrotreated light (64742-47-8) | | |
| LD50 Oral Rat | > 5000 mg/kg | |
| LD50 Dermal Rabbit | > 2000 mg/kg | |
| LC50 Inhalation Rat | > 5.2 mg/l/4h | |
| Isopropyl alcohol (67-63-0) | | |
| IARC Group | 3 | |
| 2-Butoxyethanol (111-76-2) | | |
| IARC Group | 3 | |
| SECTION 12: ECOLOGICAL INFORMATION | | |
| Toxicity | | |

Toxicity

Ecology - General: Not classified.

| Isopropyl alcohol (67-63-0) | | |
|---|---|--|
| LC50 Fish 1 | 9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) | |
| EC50 Daphnia 1 | 13299 mg/l (Exposure time: 48 h - Species: Daphnia magna) | |
| EC50 Other Aquatic Organisms 1 | 1000 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus) | |
| LC50 Fish 2 | 11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) | |
| EC50 Other Aquatic Organisms 2 | 1000 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus) | |
| 2-Butoxyethanol (111-76-2) | | |
| LC50 Fish 1 | 1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) | |
| EC50 Daphnia 1 | 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna) | |
| LC50 Fish 2 | 2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus) | |
| Petroleum distillates, hydrotreated light | (64742-47-8) | |
| LC50 Fish 1 | 45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) | |
| LC50 Fish 2 | 2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) | |
| Persistence and Degradability | | |
| Non-Skid Deck Wax | | |
| Persistence and Degradability | Not established. | |
| Bioaccumulative Potential | | |
| Non-Skid Deck Wax | | |
| | | |

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| Bioaccumulative Potential | Not established. |
|--|------------------|
| Isopropyl alcohol (67-63-0) | |
| Log Pow | 0.05 (at 25 °C) |
| 2-Butoxyethanol (111-76-2) | |
| Log Pow | 0.81 (at 25 °C) |
| Petroleum distillates, hydrotreated light (64742-47-8) | |
| BCF Fish 1 | 61 - 159 |
| | |

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

| In Accordance with DOT | Not regulated for transport |
|-------------------------|-----------------------------|
| Marine Pollutant: No | |
| In Accordance with IMDG | Not regulated for transport |
| Marine Pollutant: No | |
| In Accordance with IATA | Not regulated for transport |
| In Accordance with TDG | Not regulated for transport |
| Marine Pollutant: No | |

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

. . .

| Non-Skid Deck Wax | | |
|--|--|--|
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard | |
| Poly(oxy-1,2-ethanediyl), .alpha[3,5-dimethyl-1-(2-methylpropyl)hexyl]omegahydroxy- (60828-78-6) | | |
| Listed on the United States TSCA (Toxic Substance | es Control Act) inventory | |
| EPA TSCA Regulatory Flag | N - N - indicates a polymeric substance containing no free-radical | |
| | initiator in its Inventory name but is considered to cover the | |
| | designated polymer made with any free-radical initiator regardless | |
| | of the amount used | |
| | XU - XU - indicates a substance exempt from reporting under the | |
| | Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA | |
| | Inventory Data Base Production and Site Reports (40 CFR 710(C)) | |
| Poly(oxy-1,2-ethanediyl), .alpha[3-[1,3,3,3-tetramethyl-1-[(trimethylsilyl)oxy]disiloxanyl]propyl]omegahydroxy- (67674-67-3) | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | | |
| EPA TSCA Regulatory Flag | XU - XU - indicates a substance exempt from reporting under the | |
| | Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA | |
| | Inventory Data Base Production and Site Reports (40 CFR 710(C)) | |
| Poly(oxy-1,2-ethanediyl), .alphasulfoomega[(1,1,3,3-tetramethylbutyl)phenoxy]-, sodium salt (55348-40-8) | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | | |
| EPA TSCA Regulatory Flag | XU - XU - indicates a substance exempt from reporting under the | |
| | Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA | |
| | Inventory Data Base Production and Site Reports (40 CFR 710(C)) | |
| Polyethylene glycol (25322-68-3) | | |
| Listed on the United States TSCA (Toxic Substance | es Control Act) inventory | |

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| EPA TSCA Regulatory Flag | XU - XU - indicates a substance exempt from reporting under the | | |
|---|---|--|--|
| -0, -0 | Inventory Update Reporting Rule, i.e. Partial Updating of the TSCA | | |
| | Inventory Data Base Production and Site Reports (40 CFR 710(C)) | | |
| Isopropyl alcohol (67-63-0) | | | |
| Listed on the United States TSCA (Toxic Substances Control Ac | ct) inventory | | |
| Subject to reporting requirements of United States SARA Sect | | | |
| SARA Section 313 - Emission Reporting | 1.0 % (only if manufactured by the strong acid process, no supplier | | |
| | notification) | | |
| 2-Butoxyethanol (111-76-2) | · · · | | |
| Listed on the United States TSCA (Toxic Substances Control Ac | ct) inventory | | |
| Petroleum distillates, hydrotreated light (64742-47-8) | | | |
| Listed on the United States TSCA (Toxic Substances Control Ac | ct) inventory | | |
| US State Regulations | | | |
| Poly(oxy-1,2-ethanediyl), .alpha[3,5-dimethyl-1-(2-methylp | ropyl)bexyl]- omega -bydroxy- (60828-78-6) | | |
| U.S Texas - Effects Screening Levels - Long Term | | | |
| U.S Texas - Effects Screening Levels - Short Term | | | |
| Polyethylene glycol (25322-68-3) | | | |
| U.S Florida - Essential Chemicals List | | | |
| U.S Minnesota - Hazardous Substance List | | | |
| U.S New Hampshire - Regulated Toxic Air Pollutants - Ambie | ent Air Levels (AALs) - 24-Hour | | |
| U.S New Hampshire - Regulated Toxic Air Pollutants - Ambie | | | |
| U.S Texas - Effects Screening Levels - Long Term | | | |
| U.S Texas - Effects Screening Levels - Short Term | | | |
| Isopropyl alcohol (67-63-0) | | | |
| U.S California - SCAQMD - Toxic Air Contaminants - Non-Can | ncer Acute | | |
| U.S California - SCAQMD - Toxic Air Contaminants - Non-Can | | | |
| U.S California - Toxic Air Contaminant List (AB 1807, AB 2728 | | | |
| U.S Connecticut - Hazardous Air Pollutants - HLVs (30 min) | - / | | |
| U.S Connecticut - Hazardous Air Pollutants - HLVs (8 hr) | | | |
| U.S Connecticut - Volatile Substances | | | |
| U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptab | ole Ambient Concentrations | | |
| U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission | Levels (ELs) | | |
| U.S Idaho - Occupational Exposure Limits - TWAs | | | |
| RTK - U.S Massachusetts - Right To Know List | | | |
| U.S Massachusetts - Toxics Use Reduction Act | | | |
| U.S Michigan - Occupational Exposure Limits - STELs | | | |
| U.S Michigan - Occupational Exposure Limits - TWAs | | | |
| U.S Minnesota - Hazardous Substance List | | | |
| U.S Minnesota - Permissible Exposure Limits - STELs | | | |
| U.S Minnesota - Permissible Exposure Limits - TWAs | | | |
| U.S New Hampshire - Regulated Toxic Air Pollutants - Ambie | | | |
| U.S New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual | | | |
| U.S New Jersey - Discharge Prevention - List of Hazardous Substances | | | |
| U.S New Jersey - Environmental Hazardous Substances List | 1 | | |
| RTK - U.S New Jersey - Right to Know Hazardous Substance I | LIST | | |
| | | | |
| U.S New Jersey - Special Health Hazards Substances List | | | |
| U.S New York - Occupational Exposure Limits - TWAs | - 1 Hour | | |
| U.S New York - Occupational Exposure Limits - TWAs U.S North Dakota - Air Pollutants - Guideline Concentrations | | | |
| U.S New York - Occupational Exposure Limits - TWAs U.S North Dakota - Air Pollutants - Guideline Concentrations U.S North Dakota - Air Pollutants - Guideline Concentrations | | | |
| U.S New York - Occupational Exposure Limits - TWAs U.S North Dakota - Air Pollutants - Guideline Concentrations U.S North Dakota - Air Pollutants - Guideline Concentrations U.S Oregon - Permissible Exposure Limits - TWAs | s - 8-Hour | | |
| U.S New York - Occupational Exposure Limits - TWAs U.S North Dakota - Air Pollutants - Guideline Concentrations U.S North Dakota - Air Pollutants - Guideline Concentrations | s - 8-Hour didate Chemicals and Chemical Groups | | |

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015) U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour U.S. - Tennessee - Occupational Exposure Limits - STELs U.S. - Tennessee - Occupational Exposure Limits - TWAs U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term U.S. - Vermont - Permissible Exposure Limits - STELs U.S. - Vermont - Permissible Exposure Limits - TWAs U.S. - Washington - Permissible Exposure Limits - STELs U.S. - Washington - Permissible Exposure Limits - TWAs 2-Butoxyethanol (111-76-2) U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728) U.S. - Colorado - Groundwater Quality Standards U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min) U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr) U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs) U.S. - Idaho - Occupational Exposure Limits - TWAs U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1 U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2 U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1 U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2 RTK - U.S. - Massachusetts - Right To Know List U.S. - Michigan - Occupational Exposure Limits - Skin Designations U.S. - Michigan - Occupational Exposure Limits - TWAs U.S. - Minnesota - Chemicals of High Concern U.S. - Minnesota - Hazardous Substance List U.S. - Minnesota - Permissible Exposure Limits - Skin Designations U.S. - Minnesota - Permissible Exposure Limits - TWAs U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual RTK - U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New Jersey - Special Health Hazards Substances List U.S. - New York - Occupational Exposure Limits - Skin Designations U.S. - New York - Occupational Exposure Limits - TWAs U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour U.S. - Oregon - Permissible Exposure Limits - Skin Designations U.S. - Oregon - Permissible Exposure Limits - TWAs U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups RTK - U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual U.S. - Tennessee - Occupational Exposure Limits - Skin Designations U.S. - Tennessee - Occupational Exposure Limits - TWAs U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term U.S. - Vermont - Permissible Exposure Limits - Skin Designations U.S. - Vermont - Permissible Exposure Limits - TWAs U.S. - Washington - Permissible Exposure Limits - Skin Designations U.S. - Washington - Permissible Exposure Limits - STELs U.S. - Washington - Permissible Exposure Limits - TWAs

U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet

U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater

U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

Petroleum distillates, hydrotreated light (64742-47-8)

U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

Canadian Regulations

Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-.omega.-hydroxy- (60828-78-6)

Listed on the Canadian DSL (Domestic Substances List)

Poly(oxy-1,2-ethanediyl), .alpha.-[3-[1,3,3,3-tetramethyl-1-[(trimethylsilyl)oxy]disiloxanyl]propyl]-.omega.-hydroxy- (67674-67-3)

Listed on the Canadian DSL (Domestic Substances List)

Poly(oxy-1,2-ethanediyl), .alpha.-sulfo-.omega.-[(1,1,3,3-tetramethylbutyl)phenoxy]-, sodium salt (55348-40-8)

Listed on the Canadian DSL (Domestic Substances List)

Polyethylene glycol (25322-68-3)

Listed on the Canadian DSL (Domestic Substances List)

Isopropyl alcohol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

2-Butoxyethanol (111-76-2)

Listed on the Canadian DSL (Domestic Substances List)

Petroleum distillates, hvdrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date

- : 03/14/2017
- **Other Information**

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR).

GHS Full Text Phrases:

| Acute Tox. 4 (Dermal) | Acute toxicity (dermal) Category 4 |
|-------------------------------------|--|
| Acute Tox. 4 (Inhalation:dust,mist) | Acute toxicity (inhalation:dust,mist) Category 4 |
| Acute Tox. 4 (Inhalation:vapor) | Acute toxicity (inhalation:vapor) Category 4 |
| Acute Tox. 4 (Oral) | Acute toxicity (oral) Category 4 |
| Aquatic Chronic 2 | Hazardous to the aquatic environment - Chronic Hazard Category 2 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment - Chronic Hazard Category 3 |
| Asp. Tox. 1 | Aspiration hazard Category 1 |
| Eye Dam. 1 | Serious eye damage/eye irritation Category 1 |
| Eye Irrit. 2A | Serious eye damage/eye irritation Category 2A |
| Flam. Liq. 2 | Flammable liquids Category 2 |
| Flam. Liq. 4 | Flammable liquids Category 4 |
| Skin Irrit. 2 | Skin corrosion/irritation Category 2 |
| STOT SE 3 | Specific target organ toxicity (single exposure) Category 3 |
| H225 | Highly flammable liquid and vapor |
| H227 | Combustible liquid |
| H302 | Harmful if swallowed |
| H304 | May be fatal if swallowed and enters airways |
| H312 | Harmful in contact with skin |
| H315 | Causes skin irritation |
| H318 | Causes serious eye damage |
| H319 | Causes serious eye irritation |
| | |

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | H332 | Harmful if inhaled |
|------|---|---|
| | H335 | May cause respiratory irritation |
| | H336 | May cause drowsiness or dizziness |
| | H411 | Toxic to aquatic life with long lasting effects |
| | H412 | Harmful to aquatic life with long lasting effects |
| | | : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given. |
| NFPA | PA Fire Hazard : 1 - Must be preheated before ignition can occur. | |
| NFPA | PA Reactivity Hazard : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water. | |

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US, Mex)