

# Self-locking shackles



## + BENEFITS

- Large range of self-locking shackles
- Head of shackle pin locked into one of the notches
- Avoids accidental release due to vibrations
- Available in various versions to suit many applications
- Forged in 316L stainless steel
- Designed and made in France



N°	Part #	Ø mm	A mm	B mm	W.L. Kg	B.L. Kg	W.L.L. Kg	Weight Kg
<b>SELF-LOCKING D SHACKLES</b>								
1	1201	4	13	8	320	700	140	0.007
	1202	5	16	10	400	1000	200	0.013
	1203	6	20	12	600	1600	320	0.022
	1204	8	26	16	1000	2700	540	0.055
	1205	10	33	20	1520	4300	860	0.098
	1206	12	39	24	2080	6000	1200	0.193
	1207*	14	47	28	2400	8000	1600	0.312

N°	Part #	Ø mm	A mm	B mm	W.L. Kg	B.L. Kg	W.L.L. Kg	Weight Kg
<b>SELF-LOCKING LONG SHACKLES</b>								
2	1211	4	22	8	320	700	140	0.008
	1212	5	29	10	400	1000	200	0.017
	1213	6	33	12	600	1600	320	0.027
	1214	8	45	16	1000	2700	540	0.066
	1215	10	55	20	1520	4300	860	0.128

N°	Part #	Ø mm	A mm	B mm	W.L. Kg	B.L. Kg	W.L.L. Kg	Weight Kg
<b>SELF-LOCKING TWISTED SHACKLE</b>								
3	1222	5	26	10	480	1100	220	0.016
	1223	6	30	12	600	1500	300	0.027
	1224	8	40	16	1000	3000	600	0.067
	1225	10	50	20	1440	4500	900	0.127

N°	Part #	Ø mm	A mm	B mm	W.L. Kg	B.L. Kg	W.L.L. Kg	Weight Kg
<b>SELF-LOCKING BOW SHACKLES</b>								
4	1241	4	18	8	320	700	140	0.009
	1242	5	23	10	400	1000	200	0.017
	1243	6	28	12	600	1500	300	0.030
	1244	8	37	16	1000	2700	540	0.068
	1245	10	47	20	1520	4300	860	0.137
	1246	12	55	24	2080	6000	1200	0.233
	1247*	16	70	32	3200	10000	2000	0.540
	1248*	20	80	40	4000	15000	3000	1.056

N°	Part #	Ø mm	A mm	B mm	W.L. Kg	B.L. Kg	W.L.L. Kg	Weight Kg
<b>SELF-LOCKING LARGE OPENING SHACKLE</b>								
5	1262	5	36	20	256	1100	220	0.016
	1263	6	42	25,5	320	1500	300	0.027
	1264	8	57	32	768	2700	540	0.067
	1265	10	72	40	1280	4000	800	0.127

N°	Part #	Ø mm	A mm	B mm	W.L. Kg	B.L. Kg	W.L.L. Kg	Weight Kg
<b>ALLEN HEAD PIN SHACKLES «D»</b>								
The head of the pin does not stick out from the shackle's body, thus eliminating any risk of snagging.								
6	1303	6	19	12	600	1600	320	0.022
	1304	8	26	16	960	2700	540	0.053
	1305	10	33	20	1440	4300	860	0.099
	1306	12	39	24	2080	5500	1100	0.187
	1363	6	42	25,5	320	1500	300	0.044
<i>(specially designed for batten cars)</i>								

N°	Part #	Ø mm	A mm	B mm	W.L. Kg	B.L. Kg	W.L.L. Kg	Weight Kg
<b>ALLEN HEAD PIN LONG SHACKLES</b>								
7	1313	6	33	12	600	1600	-	0.027
	1314	8	45	16	1000	2700	-	0.066

N°	Part #	Ø mm	A mm	B mm	W.L. Kg	B.L. Kg	W.L.L. Kg	Weight Kg
<b>ALLEN HEAD PIN SHACKLES «BOW»</b>								
The head of the pin does not stick out from the shackle's body, thus eliminating any risk of snagging.								
8	1343	6	27	12	600	1500	300	0.029
	1344	8	37	16	960	2700	540	0.067
	1345	10	47	20	1440	4300	860	0.133
	1346	12	55	24	2080	6000	1200	0.222


N°	Part #	Ø mm	A mm	B mm	W.L. Kg	B.L. Kg	W.L.L. Kg	Weight Kg
<b>TACK SHACKLES</b>								
These shackles are specially designed for adjustment to the width of goosenecks.								
9	1233	6	45	16	520	1500	-	0.048
	1234	8	59	21	800	2300	-	0.110

WL: working load - BL: breaking load  
Parts # 1247, 1248 and 1207 are not self-locking shackles.

1



2



3



4



5



6



7



8



9



Working Load (WL): for nautical applications.



Working Load Limit (WLL): for industrial applications only.  
The safety factor is 5 times the breaking load. WLL = Breaking load / 5